

Pinpoint a potential radioactive source quickly and safely with a RC22 or RC23 Wand

- Fully automatic and easy to use
- Light weight
- Extendible for longer reach
- Easy to read backlit display
- Quick response time with variable alarm tone



RC22 & 23 WAND

TELESCOPIC RADIATION DETECTOR

Fully Automatic and Operator Friendly

The RC22 and RC23 were designed to allow fast and easy inspection of areas, containers or vehicles that may contain radioactive material. Upon startup, the unit will perform a background check and automatically set an alarm threshold for the user. In only seconds the RC22 and RC23 is ready for use.

Easy to Read Display with Audible Alarm

When radiation is detected, the display will immediately show the increasing radiation levels. An audio alarm will also be activated to help locate the exact source of the radiation. The tone varies based upon the proximity and intensity of the radioactive source.

Available In Two Lengths and Two Head Sizes

RC22 is telescopic for a reach of 49" (124.5cm) to 99" (251.5cm). The telescopic pole serves two functions, one is to reach and scan an area that would normally be out of reach, and the second is to provide a safer operating distance between you and a potential radioactive source.

The Wand is available in two different detector head sizes. The RC22 has a detector head size of 2" (5.1cm) for a total volume of 193cc. For greater sensitivity, the RC23 has a detector head size of 3" (7.6cm) for a total volume of 442cc.



RC22 & 23 Specifications:

Display:

- Large 2.17" (55mm) x 2.17" (55mm) backlit display LCD display.
- Display radiation level in selected unit of measurement, battery life, background level, and alarm threshold

Operation:

- Single button activation automatically sets audio alarm threshold level and displays unit of measurements (CPS, Sv/h, R/h)

Energy Response Range:

- From 30Kev – 2.0Mev

Temperature Range:

- -10°C to +50°C (+14°F to +122°F)

Battery:

- 2 sets of NiMH 10,000 mA/h rechargeable or 2 x size "D" cell batteries

Each RC22 and RC23 Package Includes:

- RC22 or RC23 fully charged and ready for use
- Carrying Case
- Rubber tip boot cover (Quantity 2)
- Earphone
- Universal battery charger
- Operation manual



Size:

Model	Head Size	Extendible Length	Weight	Detector Size
RC22 Short	2" (5.1cm)	49" (124.5cm) to 68" (172.7cm)	5.2 lbs (2.36 kg)	193 cc
RC22 Long	2" (5.1cm)	68" (172.7cm) to 99" (251.5cm)	5.4 lbs (2.72 kg)	193 cc
RC23	3" (7.6cm)	49" (124.5cm) to 68" (172.7cm)	6.0 lbs (2.45 kg)	442 cc



Corporate Head Office

Scott Aikin
 Saikin@radcommsystems.com
 Jeff Adams
 jadams@radcommsystems.com
 2931 Portland Drive
 Oakville, ON Canada L6H 5S4
 Tel. +1 (905) 829-8290
 Toll Free: 1 (800) 588-5229
 Fax: +1 (905) 829-1406

USA

Joshua Hunter
 jhunter@radcommsystems.com
 602 E. Lincolnway Ave.
 Valparaiso, IN USA 46383
 Tel. +1 (773) 680-8430
 Toll Free: 1 (800) 588-5229
 Fax: +1 (219) 510-5764

Europe

Wim van Hove
 wim.van.hove@radcommeurope.com
 Watertorenweg 32, 2230 Herselt, Belgium
 Tel. +32.14.75.02.13 Fax: +32.14.75.02.16

China

Zhenhau Wang
 wang.zhenhau@ehc-global.com
 212-215 Malu Industrial Park, No. 58
 Chen Bao Rd., Jiading
 Shanghai, 201801, China
 Tel. +86-21-69153031
 Fax: +86-21-69153231

Latin America

Eduardo Ballesteros
 analiticacontrol@prodgjny.net.mx
 Amatista No.27, El Pedregal
 Atizapan de Zaragoza, 52948, Estado De Mexico
 Tel: (52) 55 5077 4633/(52) 55 3615 4910

Black Sea

Osman Tureyyen
 metkim@metkim.com
 Kavacik, Onarimli Sokak
 No 9 Altay Han
 Daire: 8 Beykoz, Istanbul, Turkey
 Tel. +90 (216) 425-1412
 Fax: +90 (216) 425-1432

India

Neelakshi Bhargava
 neelakshi@radcommsystems.co.in
 1 Radhey Shyam Park, Parwana Road
 Delhi 110051 India
 Tel. +91-971-767-1924
 Fax: +91-852-707-7118