

Prevent costly radioactive contamination of your scrap yard, steel plant, recycling plant, equipment, product and personnel with the RC4000 series vehicle radiation detection system!

- Innovative Design with Multiple Detector Sizes
- Energy Specific Alarm and Background Statistical Analyses
- Real-Time Density Tracking Algorithm
- Remote calibration software. No source needed.
- Network Capability with Email
- Easy to install. User friendly. Easy to operate.



RC4000

VEHICLE RADIATION DETECTION SYSTEMS


Detection of Radioactivity in High Density Materials

The RC4000 series of radiation detection systems have been designed to detect very low Gamma Ray emissions in high density materials. The vehicle size and type will help determine the appropriate panel size and configuration. The RC4000 is supplied in a variety of detector panel sizes with any configuration with up to 8 detector panels. The RC4000 detection systems all utilize RadComm's high quality Polyvinyl Toluene (PVT) scintillators, electronics and Photomultiplier Tubes (PMT's).



Simplified System Operation

The RC4000 utilizes real-time statistical algorithms that are based on Gamma Energy Distribution to ensure alarm thresholds levels are optimized. The RC4000 utilizes a User Friendly Graphical interface allowing the operator to easily move through the wide range of User options. All detailed Clean Scan, Testing and Alarms records are stored on the internal hard drive and can be easily retrieved and interpreted as required.



Remote System Access

The RC4000 Controller is equipped with a network adaptor allowing remote monitoring, data retrieval and maintenance functions. The internal software and hardware designs are extremely flexible allowing remote software updates and electronic hardware adjustments when necessary. Supervisors can monitor the system operation in real-time to ensure normal system operation is maintained. Also, with a network connection the system has the capability of emailing alarms and system malfunctions.



The 4000 series consists of:

- Detector assemblies (1-8 panels)
- RadLink embedded controller
- Smart Infrared presence sensors
- Large touch screen monitor
- Remote communications package (optional)



RadLink Controller features

- Touchscreen LCD monitor
- Large storage capacity for system operational information and alarms
- Easy to follow multilingual menu outlines and descriptions
- Multi-level security password control
- Detailed alarm data storage
- Manual scanning for pinpointing source location within the vehicle's load
- Easy to set alarm configuration menu
- Network access for remote service and monitoring
- Radiation levels displayed (mR/h, nSv/h, cps)
- Vehicle speed measurement in Km/h or mph
- Ambient temperature displayed in Celsius and Fahrenheit
- Adjustable audio alarm
- Counter for number of scans in a 24 hour period for incoming and outgoing scans
- Detailed alarm information displayed and stored after every alarm
- Various String Outputs
- Configurable email reporting
- Adaptable for specific customer needs

Detector features

- Large premium grade PVT scintillators
- 34.3 to 69 liters PVT volumes available (single panel)
- Low density shield on face of detector panel
- Dual layer thermal insulation protection -20°C (-4°F) to +55°C (131°F)
- High signal to noise ratio PMTs (up to 2)
- High speed micro-controller with programmable CPLD technology for signal/alarm analysis
- Dual input high speed pulse processor
- Noise reduction hardware/software
- Background characterization for variable ambient background suppression
- Smart infrared vehicle presence with speed monitoring
- 8 output drivers (24Vdc@50mA) for remote indicators
- Internal non-radioactive test source for detailed and repeatable system checks
- 24Vdc input voltage @2.3A (8 Panels)
- System auto-stabilization & remote calibration
- Suitable for Vehicle, Rail, Charge Bucket, Offgas, Conveyor Systems

Options

- Camera
- External alarms
- Supervisory Software
- Neutron Detector

Respose/Sensitivity

Energy range: 20KeV to 3.0MeV (incident)

Model#	RC4069	RC4110	RC4138
**System Size (in ³)	4,216	5,264	8,432
**System Size (L)	69	91	138
PER/Panel Size (in ²)	2,108	2,632	4,216
PER/Panel Size (L)	34.5	45.5	69
# of PMT's/panel	1	2	2
*Detection Capability/Overall Sensitivity- Unshielded Source (Shielded Source)	1.6uCi (58mCi)	1.4uCi (50mCi)	1.1uCi (41.mCi)
* Radiation measurement of ¹³⁷ Cs (point source) at 1 meter from the face of the detector (the radiation exposure level is comparable to a 75mmx150mm ¹³⁷ Cs lead sealed source buried in 65 lbs/ft ³ (1 g/cm ³) of scrap metal)			
** System size based on 2 panels. Systems may be expanded with additional panels			



Corporate Head Office

Scott Aikin
 Saikin@radcommsystems.com
 Jeff Adams
 jadams@radcommsystems.com
 2931 Portland Drive
 Oakville, ON Canada L6H 5S4
 Tel. +1 (905) 829-8290
 Toll Free: 1 (800) 588-5229
 Fax: +1 (905) 829-1406

USA

Joshua Hunter
 jhunter@radcommsystems.com
 602 E. Lincolnway Ave.
 Valparaiso, IN USA 46383
 Tel. +1 (773) 680-8430
 Toll Free: 1 (800) 588-5229
 Fax: +1 (219) 510-5764

Europe

Wim van Hove
 wim.van.hove@radcommeurope.com
 Watertorenweg 32, 2230 Herselt, Belgium
 Tel. +32.14.75.02.13 Fax: +32.14.75.02.16

China

Zhenhau Wang
 wang.zhenhau@ehc-global.com
 212-215 Malu Industrial Park, No. 58
 Chen Bao Rd., Jiading
 Shanghai, 201801, China
 Tel. +86-21-69153031
 Fax: +86-21-69153231

Latin America

Eduardo Ballesteros
 analiticacontrol@prodgjny.net.mx
 Amatista No.27, El Pedregal
 Atizapan de Zaragoza, 52948, Estado De Mexico
 Tel: (52) 55 5077 4633/(52) 55 3615 4910

Black Sea

Osman Tureyyen
 metkim@metkim.com
 Kavacik, Onarimli Sokak
 No 9 Altay Han
 Daire: 8 Beykoz, Istanbul, Turkey
 Tel. +90 (216) 425-1412
 Fax: +90 (216) 425-1432

India

Neelakshi Bhargava
 neelakshi@radcommsystems.co.in
 1 Radhey Shyam Park, Parwana Road
 Delhi 110051 India
 Tel. +91-971-767-1924
 Fax: +91-852-707-7118